

LED Lighting Product Catalogue

Street, industrial, architectural, ATEX, emergency, RGB DMX, beacon and aviation luminaires for the UAE and the Gulf region.

192 products · 8 families · technical datasheets on request.



About this catalogue

EcoSolaris supplies and installs professional lighting across the United Arab Emirates. This catalogue covers 192 LED luminaires, grouped into 8 families, from road and industrial floodlighting to architectural facade systems, hazardous-area fittings and certified airfield lighting.

The range is designed and manufactured in Europe and specified for Gulf conditions: high ambient temperature, dust, humidity and coastal salt air. Housings are die-cast aluminium, sealing runs from IP65 to IP68, and surge protection is fitted as standard on outdoor families.

Optics, colour temperature, beam angle, finish and control gear are selected per project. DALI, 1-10V, DMX512 and wireless dimming are available across most families. Photometric files are supplied on request for lighting calculations.

Every product has its own technical datasheet, available for download from the product page on www.ecosolaris.ae. Prices are quoted per project, together with lead time. The minimum order is 10 pieces per product.

LED Street Floodlights

LED Industrial Floodlights

Indoor LED Lighting

Emergency LED Lighting

RGB DMX LED Lighting

Commercial LED Lighting

Interior Architectural Lighting

Exterior Architectural Lighting

Request a quotation or a lighting design

PHOTOVOLTAIC ENERGY L.L.C. · Canal Highs 4001, P.O. Box 25314, Dubai, UAE

Email: contact@ecosolaris.ae · Tel / WhatsApp: +971 58 511 8662

Web: www.ecosolaris.ae

Contents

01	LED Street Floodlights	19 products
02	LED Industrial Floodlights	7 products
03	Indoor LED Lighting	6 products
04	Emergency LED Lighting	5 products
05	RGB DMX LED Lighting	12 products
06	Commercial LED Lighting	2 products
07	Interior Architectural Lighting	49 products
08	Exterior Architectural Lighting	32 products


01

LED Street Floodlights

LED street floodlights for roads, highways, interchanges, bridges and large outdoor areas. Asymmetric road optics keep light on the carriageway and limit glare and spill, while die-cast aluminium housings and IP66 sealing handle heat, sand and humidity across the Gulf. Power ranges typically span 30 W to 400 W with efficacies above 140 lm/W, selectable colour temperature and optional DALI or 1-10V dimming for night-time setback. Surge protection up to 10 kV protects the driver on long feeder runs.

19 products in this family. Individual datasheets available on www.ecosolaris.ae.

LED Street Floodlights



ECO-LED-480

Titan Pedestrian Crossing LED Lighting System 250-490W

Complete crossing lighting and warning system built from Titan floodlights with OSRAM LEDs and dedicated elliptical...

Components: Titan floodlights + signal panels with amber lamps

Housing material: Anodised aluminium

Light source: OSRAM LEDs, dedicated elliptical focusing

Total power: 250 W / 1.2



ECO-LED-459

Topaz Street LED Floodlight 12-48 LEDs 30-200W

Modular street floodlight with 12, 24, 36 or 48 high power OSRAM LEDs, from 30 to 200 W, with external driver...

Housing material:

Electrostatically powder coated aluminium

Housing colour: Grey (standard)

Number of LEDs: 12 / 24 / 36 / 48



ECO-LED-426

Proton SP II Street LED Floodlight 18 LEDs 45-60W

Light 2 kg street floodlight with 18 high power OSRAM LEDs and 45-60 W consumption, supplied at 230 V AC or...

Housing material:

Electrostatically powder coated aluminium

Diffuser: Clear polycarbonate, UV protected

Housing colour: Other colours available on request



ECO-LED-424

Perla Park LED Lamp 20-43W with PMMA Globe

Park luminaire with a semi transparent spherical PMMA globe and omnidirectional distribution, mounted on a...

Housing material:

Electrostatically powder coated aluminium

Diffuser: Semi transparent spherical PMMA globe

Number of LEDs: 8 / 12 / 1 COB
Total power: 20 W / 28 W / 43 W

LED Street Floodlights



ECO-LED-422

ASTRO Astronomical Time Switch for Street Lighting

Control time switch with astronomical programme for public lighting, adjusting the on and off times daily to sunset...

Type: Control time switch with astronomical programme

Versions: 1 or 3 relays, individual programme per relay

Switching current: 16 A per channel

Rated load: 2000 VA



ECO-LED-413

Proton SP II Street LED Floodlight 36 LEDs 90-120W

Street floodlight with 36 high power OSRAM LEDs and 90-120 W consumption, approved for outdoor and indoor use...

Housing material:

Electrostatically powder coated aluminium

Diffuser: Clear polycarbonate, UV protected

Housing colour: Grey (standard)



ECO-LED-410

Proton SP II Street LED Floodlight 24 LEDs 60-90W

Street floodlight with 24 high power OSRAM LEDs and 60-90 W consumption, approved for outdoor and indoor use...

Housing material:

Electrostatically powder coated aluminium

Diffuser: Clear polycarbonate, UV protected

Housing colour: Grey (standard)



ECO-LED-367

Proton S Street LED Floodlight 3 COB LEDs 100-150W

Floodlight of 100-150 W with three Bridgelux COB LEDs and outdoor grade silicone lenses, with an elliptical asymmetric...

Housing material: Anodised aluminium, electrostatically powder coated

Diffuser: 3 mm clear polycarbonate, UV protected

Housing colour: Other colours available on request

LED Street Floodlights



ECO-LED-365

Proton S Street LED Floodlight 2 COB LEDs 30-50W

Floodlight with two Bridgelux COB LEDs and outdoor grade silicone lenses, with an elliptical asymmetric beam a...

Housing material: Anodised aluminium, electrostatically powder coated
Diffuser: 3 mm clear polycarbonate, UV protected
Housing colour: Other colours available on request



ECO-LED-363

Proton S Street LED Floodlight 1 COB LED 30-50W

Compact floodlight with one 30-50 W Bridgelux COB LED and an outdoor grade silicone lens, with an elliptical...

Housing material: Anodised aluminium, electrostatically powder coated
Diffuser: 3 mm clear polycarbonate, UV protected
Housing colour: Other colours available on request



ECO-LED-248

Proton II Street LED Floodlight 24 LEDs 80W

Street floodlight with 24 high power OSRAM LEDs and 80 W consumption, designed for ME4 class roads. Wide 90-260 V A...

Housing material: Extruded aluminium, electrostatically powder coated
Diffuser: 3 mm clear polycarbonate, UV protected
Housing colour: Other colours available on request



ECO-LED-247

Proton II Street LED Floodlight 36 LEDs 90W

Street floodlight with 36 high power OSRAM LEDs and 90 W consumption, designed for ME4 class roads. Elliptical...

Housing material: Extruded aluminium, electrostatically powder coated
Diffuser: 3 mm clear polycarbonate, UV protected
Housing colour: Grey (standard)

LED Street Floodlights



ECO-LED-246

Proton II Street LED Floodlight 45 LEDs 120W

Street floodlight with 45 high power OSRAM LEDs and 120 W consumption, designed for ME4 class roads. Elliptical...

Housing material: Extruded aluminium, electrostatically powder coated

Diffuser: 3 mm clear polycarbonate, UV protected

Housing colour: Grey (standard)



ECO-LED-242

Proton SS II Solar Street LED Floodlight 12 LEDs 30W 12V

Street floodlight supplied at 12 V DC, suitable for photovoltaic systems with battery storage. 12 high power OSRAM LEDs, ...

Housing material:

Electrostatically powder coated aluminium

Diffuser: Clear polycarbonate, UV protected

Housing colour: Other colours available on request



ECO-LED-232

Proton SP II Street LED Floodlight 6 LEDs 15-20W

Compact street floodlight with 6 high power OSRAM LEDs and 15-20 W consumption, with the power supply built into the...

Housing material:

Electrostatically powder coated aluminium

Diffuser: Clear polycarbonate, UV protected

Housing colour: Other colours available on request



ECO-LED-101

Proton II Street LED Floodlight 12 LEDs 30W 3360 lm

Street floodlight with 12 high-intensity OSRAM LEDs (2.5W each), 30W total and 3360 lm at a minimum of 112 lm/W....

Luminaire type: Street floodlight, Proton II series

Number of LEDs: 12

Light source: High-intensity OSRAM LEDs

Total power: 30W (12 x 2.5W)
Luminous flux 3360 lm

LED Street Floodlights



ECO-LED-37

Moon Park LED Luminaire Spherical Diffuser 20-30W

Globe luminaire with a semi-translucent PMMA spherical diffuser, using 8 LEDs, 12 LEDs or 1 OSRAM COB LED (100,000 hours)

Luminaire type: Park luminaire with spherical diffuser, Moon series

Number of LEDs: 8 / 12 / 1 COB

Light source: High-power OSRAM LEDs, 100,000 hours

Total power: 20W / 30W



ECO-LED-36

Proton SS II Solar Street LED Floodlight 24 LEDs 60W

Solar-powered street floodlight with 24 high-power OSRAM LEDs (100,000 hours), 60W and a minimum efficacy of 110 lm/W

Luminaire type: Solar-powered street floodlight, Proton SS II series

Number of LEDs: 24

Light source: High-power OSRAM LEDs, 100,000 hours

Total power: 60W



ECO-LED-33

Proton SP II Street LED Floodlight 12 LEDs 30-45W

Compact street floodlight with 12 high-power OSRAM LEDs (100,000 hours), 30-45W, minimum efficacy 110 lm/W

Luminaire type: Street floodlight, Proton SP II series

Number of LEDs: 12

Light source: High-power OSRAM LEDs, 100,000 hours

Total power: 30-45W

02

LED Industrial Floodlights

High-output LED floodlights and high bays for warehouses, production halls, ports, yards, quarries and sports facilities. Built for continuous duty at high ambient temperature, with heavy aluminium heatsinks, toughened glass and IP66 protection. Beam angles from narrow spot to wide flood let you light a stack, an aisle or an entire yard from few positions, keeping mounting structures and maintenance access to a minimum.

7 products in this family. Individual datasheets available on www.ecosolaris.ae.

LED Industrial Floodlights



ECO-LED-395

Apolo II Industrial LED Floodlight 9 COB LEDs 300-450W

High-power industrial floodlight with 9 Bridgelux COB LEDs, 300-450W, 45,000 lm luminous flux and minimum 110 lm/W...

Body material: Extruded aluminium, electrostatically painted

Diffuser: Clear polycarbonate, UV protected

Body colour: Other colours available on request



ECO-LED-327

Astro II LED Floodlight for Petrol Stations 2 COB LEDs 100W

Canopy floodlight with 2 wide-distribution Bridgelux COB LEDs, 100W, for recessing into petrol station canopies...

Body material: Electrostatically painted aluminium

Diffuser: Clear polycarbonate, UV protected

Body colour: Other colours available on request

Light source: 2 Bridgelux COB



ECO-LED-326

Astro II LED Floodlight for Petrol Stations 1 COB LED 50W

Canopy floodlight with 1 wide-distribution Bridgelux COB LED, 50W, for recessed mounting in petrol station canopies...

Body material: Electrostatically painted aluminium

Diffuser: Clear polycarbonate, UV protected

Body colour: Other colours available on request

Light source: 1 Bridgelux COB



ECO-LED-304

Apolo II Industrial LED Floodlight 1 COB LED 30-50W

Compact version of the series: 1 Bridgelux COB LED, 30-50W, minimum 110 lm/W, a 270 x 135 x 150 mm extruded...

Body material: Extruded aluminium, electrostatically painted

Diffuser: Clear polycarbonate, UV protected

Body colour: Other colours available on request

LED Industrial Floodlights



ECO-LED-302

Apo II Industrial LED Floodlight 2 COB LEDs 60-100W

Industrial floodlight with 2 Bridgelux COB LEDs, 60-100W, minimum 110 lm/W, a 520 mm extruded aluminium body wit...

Body material: Extruded aluminium, electrostatically painted

Diffuser: Clear polycarbonate, UV protected

Body colour: Other colours available on request



ECO-LED-300

Apo II Industrial LED Floodlight 3 COB LEDs 100-150W

Linear industrial floodlight with 3 Bridgelux COB LEDs, 100-150W, minimum 110 lm/W, a 770 mm extruded aluminium...

Body material: Extruded aluminium, electrostatically painted

Diffuser: Clear polycarbonate, UV protected

Body colour: Other colours available on request



ECO-LED-294

Apo II Industrial LED Floodlight 4 COB LEDs 150-200W

Industrial floodlight with 4 high-power Bridgelux COB LEDs, 150-200W, efficacy of minimum 110 lm/W. Extruded...

Body material: Extruded aluminium, electrostatically painted

Diffuser: Clear polycarbonate, UV protected

Body colour: Other colours available on request

03

Indoor LED Lighting

Panels, linear fittings, downlights and surface luminaires for offices, retail, schools, clinics and technical rooms. Low-glare optics (UGR<19 on selected models) and high colour rendering make them suitable for workplaces governed by EN 12464-1.

6 products in this family. Individual datasheets available on www.ecosolaris.ae.

Indoor LED Lighting



ECO-LED-434

Display II LED Ceiling Panel 300x1200 mm 45W

Elongated 300 x 1200 x 16 mm ceiling panel rated 45W, for corridors, classrooms and production areas. White...

Body material: Electrostatically painted aluminium

Diffuser: Clear polycarbonate, UV resistant

Body colour: Standard white

Total power: 45W

Luminous efficacy: Min. 100



ECO-LED-433

Display II LED Ceiling Panel 300x600 mm 22W

Narrow 300 x 600 x 16 mm ceiling panel rated 22W for half-module ceiling tiles. White anodised aluminium body wit...

Body material: Anodised aluminium, electrostatically painted

Diffuser: Clear polycarbonate, UV resistant

Body colour: Standard white

Total power: 22W



ECO-LED-389

Cerber Bidirectional LED Spotlight 6 LEDs 6-18W

Accent spotlight emitting in two directions, each with its own colour and beam. 6 OSRAM LEDs, 6W or 18W, white...

Body material: Electrostatically painted aluminium

Diffuser: Clear polycarbonate

Body colour: Standard black; white, grey or another RAL on request

Total power: 6 OSRAM LEDs



ECO-LED-298

Display II LED Ceiling Panel 600x600 mm 45W

600 x 600 x 16 mm ceiling panel rated 45W, replacing luminaires with four 18W fluorescent tubes. White...

Body material: Electrostatically painted aluminium

Diffuser: Clear polycarbonate, UV resistant

Body colour: Standard white

Total power: 45W

Luminous efficacy: Min. 100

Indoor LED Lighting



ECO-LED-46

Oasis LED Wall Light for Bathrooms and Wet Areas 10-20W

Wall light with chromed metal body and satin glass diffuser, with a protected optical compartment for humid room...

Body material: Chromed metal
Diffuser: Satin glass
Body colour: Standard grey
Light source: Samsung LEDs
Total power: 10W | 20W



ECO-LED-22

Linea Linear LED Bar 12V for Recessed Lighting

Modular linear profile in anodised aluminium with OSRAM LEDs, in 250 mm segments up to 2000 mm, 2...

Body material: Anodised aluminium
Diffuser: Clear or matt PMMA
Body colour: Standard grey
Light source: OSRAM LEDs
Power: 2W per 250 mm module; 20W/m

04

Emergency LED Lighting

Emergency and escape-route luminaires, exit signs and centrally supplied fittings that keep a building safe when mains power fails. Maintained and non-maintained versions with 1 to 3 hour autonomy, self-test and addressable options.

5 products in this family. Individual datasheets available on www.ecosolaris.ae.

Emergency LED Lighting



ECO-LED-409

LS-011 LED Safety Panel with 20 LEDs 2W

Maintained safety luminaire with a large luminous panel, 20 cool white 5000K LEDs and a viewing distance up to 30 m....

Housing material: Electrostatically painted aluminium
Housing colour: White (standard)
Diffuser: Clear UV-protected polycarbonate



ECO-LED-345

LS-09 Recessed LED Safety Luminaire without Emergency Kit

Safety luminaire without emergency kit, recessed into a vertical plasterboard wall. Four high-power OSRAM LEDs in c...

Housing material: Electrostatically painted aluminium
Housing colour: White (standard)
Diffuser: Clear polycarbonate with silver-grey film



ECO-LED-341

LS-07 LED Safety Luminaire with 2W Emergency Kit

Safety luminaire with emergency kit, supplied at 230V AC and switched to batteries when the mains fail...

Housing material: Electrostatically painted aluminium
Housing colour: Grey (standard)
Diffuser: Clear polycarbonate with silver-grey film



ECO-LED-250

LS-06 Recessed LED Emergency Luminaire 2W

Recessed plasterboard escape luminaire with two curved plastic plates working on the fibre optic principle and 4 hig...

Operating principle: Fibre optic, two curved plates
Mounting: Recessed in plasterboard
Housing material: Anodised aluminium / electrostatically painted steel

Emergency LED Lighting



ECO-LED-95

LS-05 Protect LED Emergency Luminaire 2W

Indoor escape luminaire with OSRAM LEDs working on the fibre optic principle through two plastic plates (green/red...

Operating principle: Fibre optic, two plastic plates

Operating mode: Permanent; batteries on mains failure

Housing material: Electrostatically painted aluminium sheet

05

RGB DMX LED Lighting

Colour-changing LED systems driven by DMX512 or RDM for facades, bridges, fountains, hospitality and entertainment venues. Pixel-level control allows video-mapped effects, while master-slave and standalone modes cover simpler schemes.

12 products in this family. Individual datasheets available on www.ecosolaris.ae.

RGB DMX LED Lighting



ECO-LED-430

Stand-Alone DMX Touch Panel for RGB LED 1024 Channels

Stand-alone DMX controller with touch panel for indoor and outdoor RGB architectural lighting. Two DMX512...

Equipment type: Stand-alone DMX controller with touch panel
Output protocol: Two DMX512 universes

Number of channels: 1024
Maximum RGB luminaires: 340, as separate addresses



ECO-LED-64

DMX RGB LED Controller with Remote 96 Addresses 4 Zones

DMX controller with remote for RGB applications, with up to 96 DMX addresses in 4 individual zones. It commands a...

Equipment type: DMX controller with remote, RGB applications
Maximum number of DMX addresses: 96
Individual zones: 4
Maximum number of RGB



ECO-LED-60

Proton RGB DMX LED Floodlight 36 LEDs 90W

Outdoor RGB floodlight of 90W with 36 OSRAM LEDs (12 x red 650 nm, 12 x green 523 nm, 12 x blue 470 nm), an integrate...

Luminaire type: Outdoor RGB floodlight, Proton series
Number of LEDs: 36 (12 x red, 12 x green, 12 x blue)
Light source: OSRAM LEDs
LED colour: Red 650 nm, green 523 nm, blue 470 nm



ECO-LED-56

Niagara Submersible Pool RGB DMX LED Floodlight 36 LEDs

Submersible pool floodlight with 36 OSRAM RGB LEDs (12 x red 650 nm, 12 x green 523 nm, 12 x blue 470 nm) and a...

Luminaire type: Submersible RGB pool floodlight, Niagara series
Number of LEDs: 36 (12 x red, 12 x green, 12 x blue)
Light source: OSRAM LEDs
LED colour: Red 650 nm, green 523 nm, blue 470 nm

RGB DMX LED Lighting



ECO-LED-55

Atlas Recessed RGB DMX LED Floodlight 24 LEDs Outdoor

In-ground recessed floodlight with 24 OSRAM RGB LEDs (8 x red 650 nm, 8 x green 523 nm, 8 x blue 470 nm) and an...

Luminaire type: Recessed RGB floodlight, Atlas series

Number of LEDs: 24 (8 x red, 8 x green, 8 x blue)

Light source: OSRAM LEDs

LED colour: Red 650 nm, green 523 nm, blue 470 nm



ECO-LED-54

Atlas Recessed RGB DMX LED Floodlight 6 LEDs Outdoor

In-ground recessed floodlight with 6 OSRAM RGB LEDs (2 x red 650 nm, 2 x green 523 nm, 2 x blue 470 nm) and an...

Luminaire type: Recessed RGB floodlight, Atlas series

Number of LEDs: 6 (2 x red, 2 x green, 2 x blue)

Light source: OSRAM LEDs

LED colour: Red 650 nm, green 523 nm, blue 470 nm



ECO-LED-53

Atlas Recessed RGB DMX LED Floodlight 3 LEDs Outdoor

In-ground recessed floodlight with 3 OSRAM RGB LEDs (red 650 nm, green 523 nm, blue 470 nm) and an integrated...

Luminaire type: Recessed RGB floodlight, Atlas series

Number of LEDs: 3 (1 x red, 1 x green, 1 x blue)

Light source: OSRAM LEDs

LED colour: Red 650 nm, green 523 nm, blue 470 nm



ECO-LED-52

Saturn Adjustable RGB DMX LED Floodlight 24 LEDs

Outdoor adjustable floodlight with 24 OSRAM RGB LEDs (8 x red 650 nm, 8 x green 523 nm, 8 x blue 470 nm) and a DMX...

Luminaire type: Adjustable RGB floodlight, Saturn series

Number of LEDs: 24 (8 x red, 8 x green, 8 x blue)

Light source: OSRAM LEDs

LED colour: Red 650 nm, green 523 nm, blue 470 nm

RGB DMX LED Lighting



ECO-LED-51

Saturn Adjustable RGB DMX LED Floodlight 6 LEDs

Outdoor adjustable floodlight with 6 OSRAM RGB LEDs (2 x red 650 nm, 2 x green 523 nm, 2 x blue 470 nm) and an...

Luminaire type: Adjustable RGB floodlight, Saturn series

Number of LEDs: 6 (2 x red, 2 x green, 2 x blue)

Light source: OSRAM LEDs

LED colour: Red 650 nm, green 523 nm, blue 470 nm



ECO-LED-50

Saturn Adjustable RGB DMX LED Floodlight 3 LEDs

Compact adjustable floodlight with 3 OSRAM RGB LEDs (red 650 nm, green 523 nm, blue 470 nm) and a DMX driver in...

Luminaire type: Adjustable RGB floodlight, Saturn series

Number of LEDs: 3 (1 x red, 1 x green, 1 x blue)

Light source: OSRAM LEDs

LED colour: Red 650 nm, green 523 nm, blue 470 nm



ECO-LED-49

Galaxy Linear RGB DMX LED Floodlight 24 LEDs

Outdoor linear RGB floodlight with 24 OSRAM LEDs (8 x red 650 nm, 8 x green 523 nm, 8 x blue 470 nm) and an...

Luminaire type: Linear RGB floodlight, Galaxy series

Number of LEDs: 24 (8 x red, 8 x green, 8 x blue)

Light source: OSRAM LEDs

LED colour: Red 650 nm, green 523 nm, blue 470 nm



ECO-LED-47

Galaxy Linear RGB DMX LED Floodlight 9 LEDs

Outdoor linear RGB floodlight with 9 OSRAM LEDs (3 x red 650 nm, 3 x green 523 nm, 3 x blue 470 nm) and a DMX driv...

Luminaire type: Linear RGB floodlight, Galaxy series

Number of LEDs: 9 (3 x red, 3 x green, 3 x blue)

Light source: OSRAM LEDs

LED colour: Red 650 nm, green 523 nm, blue 470 nm

06

Commercial LED Lighting

Display and accent lighting for shops, showrooms, malls and hospitality, where colour rendering and beam control decide how merchandise and materials look. Track, spot and recessed options with tight beam tolerance.

2 products in this family. Individual datasheets available on www.ecosolaris.ae.

Commercial LED Lighting



ECO-LED-371

Celest II LED Track Spotlight 1 COB LED 30W

Indoor accent spotlight with a single 30W Bridgelux COB LED, mounted on a 2 m track with 3 circuits. Aluminium body for...

Housing material: Anodised aluminium and PVC; external parts in stainless steel
Housing colour: White (standard)
Diffuser: Plexiglass
Light source: 1 Bridgelux COB



ECO-LED-44

Celest Active Cooling LED Spotlight CRI 95

Indoor LED spotlight with an active cooling system, intended for accent lighting in shop windows and display areas....

Product type: Indoor LED spotlight with active cooling
Series: Celest
Light colour version 1: Warm white
Light colour version 2: Neutral white

07

Interior Architectural Lighting

Architectural-grade interior families for lobbies, museums, galleries, hospitality and premium retail: linear systems, trimless recessed profiles, adjustable spots and modular downlights with a common visual language. Tight LED binning, high CRI and deep anti-glare optics keep the light quality consistent while the fitting stays visually discreet.

49 products in this family. Individual datasheets available on www.ecosolaris.ae.

Interior Architectural Lighting

ECO-LED-63579

Unoluce Suspended Linear LED System 18.4W for Offices

Suspended 18.4 W linear luminaire for offices, with UGR below 10 and CRI above 90. Extruded aluminium body of...

Mounting type: Suspended (pendant), fixing system included
Material: Extruded aluminium, lens diffuser with plastic screen
Available finishes: White RAL9010, black
Power: 18.4 W

ECO-LED-56752

Titan 12 Industrial LED Floodlight 60W Indoor

60 W industrial floodlight with an extruded aluminium housing of 167 x 150 x 306 mm, integral power supply and...

Mounting type: Flat surface or pole, adjustable
Material: Extruded aluminium
Finish: Grey RAL7040, electrostatic powder coated
Power: 60 W
Luminous flux: 7326 7744 lm



ECO-LED-57321

Zoomix Adjustable LED Spotlight 12W for 48V Magnetic Track

Adjustable aluminium spotlight, 65 x 135 x 55.5 mm, for 48 V DC magnetic track, with a zoom optic adjustable betwe...

Mounting type: 48 V DC magnetic track, adjustable head
Material: Aluminium
Finish: Black
Power: 12 W
Luminous flux: 977 lm



ECO-LED-61936


Pluto Orbit Mini Adjustable Recessed LED Spotlight 4W

Recessed accent spotlight with a tilting head, 4 W and 52 x 25 mm, in aluminium with a polycarbonate diffuser. Narro...

Mounting type: Recessed, adjustable
Material: Aluminium, polycarbonate diffuser
Finish: Grey RAL7040
Power: 4 W
Luminous flux: 364 337 lm



Interior Architectural Lighting



ECO-LED-61975

Pluto Core Mini Recessed LED Spotlight 4W

Miniature recessed spotlight, 4 W, 40 x 26 mm and 0.048 kg, with a grey aluminium body and clear polycarbonate...

Mounting type: Recessed, fixed

Material: Aluminium, clear polycarbonate diffuser

Finish: Grey RAL7040

Power: 4 W

Luminous flux: 194-327 lm (depending on optic)



ECO-LED-57340

Luminex Flexible LED Neon 12W for 48V Magnetic Track

Flexible silicone neon module, 25 x 1000 mm, for 48 V DC magnetic track, with light distribution through 360...

Mounting type: 48 V DC magnetic track

Material: Silicone

Finish: Black

Power: 12 W

Luminous flux: 1211 lm



ECO-LED-63614

Duoluce Bidirectional Linear LED System 34W for Offices

Suspended 34 W linear luminaire with bidirectional emission (towards the working plane and the ceiling), UGR...

Mounting type: Suspended (pendant), fixing system included

Material: Extruded aluminium, lens diffuser with plastic screen

Available finishes: White RAL9010, black

Power: 34 W



ECO-LED-57078

Eclipsar Suspended LED Luminaire 15W Indoor

Cylindrical LED pendant of 63 x 300 mm, 15 W, flux 1,252 lm (narrow optic) or 1,360 lm (wide optic), efficacy 83-92...

Mounting type: Suspended

Housing material: Aluminium

Finish: Black (RAL9010)

Power: 15 W

Luminous flux: 1,252 - 1,360 lm

Interior Architectural Lighting



ECO-LED-57587

Astraline G20 Slim Magnetic Track Linear LED Luminaire 20W

Linear LED module of 445 mm for slim 48 V DC magnetic track, 20 W, 1,399 lm, 70 lm/W, 30 degrees beam angle, CCT...

Mounting type: Slim 48 V DC magnetic track

Housing material: Aluminium

Finish: Black (RAL9010)

Power: 20 W

Luminous flux: 1,399 lm



ECO-LED-57370

Rory Low Voltage 48V Magnetic Track LED Spotlight 10W

LED spotlight for surface 48 V DC magnetic track, 10 W, 838 lm, 61 lm/W, 24 degrees light distribution, CCT 3000/4000 ...

Mounting type: Surface 48 V DC magnetic track

Housing material: Aluminium

Finish: Black (RAL9010)

Power: 10 W

Luminous flux: 838 lm



ECO-LED-57385

Rory A25 220V Track LED Spotlight 25W Zoom

LED spotlight with zoom optic for 220-240 V AC track, 25 W, adjustable 15-50 degrees, flux 875-1,500 lm, 60 lm/W, CCT...

Mounting type: 220-240 V AC track

Housing material: Aluminium

Finish: Black (RAL9010)

Power: 25 W

Luminous flux: 875 - 1,500 lm



ECO-LED-57408

Rory A15 220V Track LED Spotlight 15W Zoom

LED spotlight with zoom optic for 220-240 V AC track, 15 W, adjustable 13-36 degrees, flux 495-855 lm, 57 lm/W, CCT...

Mounting type: 220-240 V AC track

Housing material: Aluminium

Finish: Black (RAL9010)

Power: 15 W

Luminous flux: 495 - 855 lm

Interior Architectural Lighting



ECO-LED-57427

Rory 30 Track LED Spotlight 220V 30W Tunable CCT

Track spotlight for 220-240 V AC systems. 30 W, 2400 to 2550 lm, 85 lm/W efficacy, tunable colour temperature,...

Mounting type: 220-240 V AC track

Housing material: Aluminium

Colour: Black (RAL9010)

Power: 30 W

Luminous flux: 2400 - 2550 lm



ECO-LED-57450

Rory 10 Track LED Spotlight 220V 10W Indoor

Track spotlight for 220-240 V AC systems. 10 W, 650 to 1235 lm depending on optic (spot, medium, wide), 54 to 88 lm/...


Mounting type: 220-240 V AC track

Housing material: Aluminium

Colour: Black (RAL9010)

Power: 10 W

Luminous flux: 650 - 1235 lm



ECO-LED-57014

Office Line 2200 Suspended LED Luminaire 80W Offices

Suspended linear LED luminaire of 2200 mm for offices, with direct and indirect emission (up and down), 80 W, 5276 lm, 6...

Mounting type: Suspended

Housing material: Anodised aluminium

Colour: Anodised black (RAL9010)

Power: 80 W

Luminous flux: 5276 lm



ECO-LED-57503

Noglo T Adjustable LED Spotlight Slim Magnetic Track 10W

Adjustable spotlight of 44x112 mm in black aluminium for 48 V DC slim magnetic track. 10 W, 702 lm, 64 lm/W, medium...

Mounting type: 48 V DC slim magnetic track, adjustable

Material: Aluminium

Colour: RAL9010 black

Power: 10 W

Luminous flux: 702 lm

Interior Architectural Lighting



ECO-LED-57526

Noglo P Linear LED Module Slim Magnetic Track 6W

Linear module of 30x300 mm in black aluminium for 48 V DC slim magnetic track. 6 W, 400 lm, 66.6 lm/W, medium optic,...

Mounting type: 48 V DC slim magnetic track

Material: Aluminium

Colour: RAL9010 black

Power: 6 W

Luminous flux: 400 lm



ECO-LED-57488

Noglo F LED Spotlight Slim Magnetic Track 6W

Fixed spotlight of 80x75 mm in black aluminium for 48 V DC slim magnetic track. 6 W, 363 lm, 60.5 lm/W, medium optic,...


Mounting type: 48 V DC slim magnetic track

Material: Aluminium

Colour: RAL9010 black

Power: 6 W

Luminous flux: 363 lm



ECO-LED-57355

Luminesse Magnetic Track LED Luminaire 48V 20W

Linear module of 900x23x40.8 mm in black aluminium, held magnetically on 48 V DC track. 20 W, 1357 lm, omnidirection...


Mounting type: 48 V DC magnetic track

Material: Aluminium

Colour: RAL9010 black

Power: 20 W

Luminous flux: 1357 lm



ECO-LED-57048

Smooth A Linear LED System 34W Wall Washer

Linear ceiling profile of 1500x44.8x83 mm in black aluminium, with asymmetric wall washer distribution. 34 ...

Mounting type: Surface ceiling mounted

Material: Aluminium

Colour: RAL9010 black

Power: 34 W

Luminous flux: 3888 lm

Interior Architectural Lighting



ECO-LED-57063

Smooth 2A Linear LED System 34W Double Asymmetric

Linear ceiling profile of 1500x44.8x83 mm in black aluminium, with double asymmetric light distribution....

Mounting type: Surface ceiling mounted

Material: Aluminium

Colour: RAL9010 black

Power: 34 W

Luminous flux: 3040 lm



ECO-LED-56995

Office Line 1100 Suspended LED Luminaire 40W Indoor

Suspended linear profile of 1100x25x100 mm in anodised black aluminium, emitting light upwards and downwards. 40 ...

Mounting type: Suspended

Material: Anodised aluminium

Colour: RAL9010 anodised black

Power: 40 W

Luminous flux: 2638 lm



ECO-LED-56230

Display Line III Surface-Mounted Linear LED Luminaire 5 Modules 65W

Surface-mounted linear LED luminaire with 5 modules, 1585 x 59 x 68.5 mm, 65 W, flux 7959-9496 lm, efficacy 122-...

Mounting type: Surface mounted

Material: Extruded aluminium

Colour: Anodised white RAL9010

Number of modules: 5

Power: 65 W



ECO-LED-56184

Display Line III Surface-Mounted Linear LED Luminaire 2 Modules 26W

Surface-mounted linear LED luminaire with 2 modules, 617 x 59 x 68.5 mm, 26 W, flux 3184-3399 lm, efficacy 122-...

Mounting type: Surface mounted

Material: Extruded aluminium

Colour: Anodised white RAL9010

Number of modules: 2

Power: 26 W

Interior Architectural Lighting



ECO-LED-56826

Titan 36 Adjustable Industrial LED Floodlight 180W

Adjustable 180 W industrial LED floodlight with a 616 mm grey RAL7040 extruded aluminium housing, IP66, IK1...

Mounting type: On a flat surface or on a pole

Material: Extruded aluminium

Colour: Grey RAL7040, electrostatically coated

Power: 180 W

Luminous flux: 22000 - 22221



ECO-LED-56791

Titan 24 Adjustable Industrial LED Floodlight 120W

Adjustable 120 W industrial LED floodlight with a grey RAL7040 extruded aluminium housing, IP66, IK10, class I...

Mounting type: On a flat surface or on a pole

Material: Extruded aluminium

Colour: Grey RAL7040, electrostatically coated

Power: 120 W

Luminous flux: 14672 - 15487



ECO-LED-57112

Invisilux W Adjustable Recessed LED Spotlight 12W

Adjustable recessed LED spotlight, 12 W, 1164 lm, 89.5 lm/W, wide 38 degree beam, CRI 90. White RAL9010...

Mounting type: Recessed in ceiling

Material: Aluminium

Colour: White RAL9010

Power: 12 W

Luminous flux: 1164 lm



ECO-LED-57127

Invisilux T Adjustable Recessed LED Spotlight 10W CRI97

Adjustable recessed LED spotlight, 10 W, CRI 97, with 15, 24 or 60 degree optics and flux of 929-1027 lm. White...

Mounting type: Recessed in ceiling

Material: Aluminium

Colour: White RAL9010

Power: 10 W

Luminous flux: 929 - 1027 lm

Interior Architectural Lighting



ECO-LED-57173

Invisilux D Recessed LED Spotlight 8W IP54

Fixed recessed LED downlight, 8 W, 635 lm, 80 lm/W, with a wide 60 degree beam. Aluminium housing in white...


Mounting type: Recessed in ceiling

Material: Aluminium

Available colours: White RAL9010, black

Power: 8 W

Luminous flux: 635 lm



ECO-LED-57097

Flexiray P Recessed LED Spotlight 6W CRI90

Fixed recessed LED spotlight, 6 W, 585 lm, with a 30 degree beam, CRI 90 and UGR 13 or less (X=4H, Y=8H). White...

Mounting type: Recessed in ceiling

Material: Aluminium

Colour: White RAL9010

Power: 6 W

Luminous flux: 585 lm



ECO-LED-57192

Flexiray S Adjustable Recessed LED Spotlight 10W

Adjustable recessed LED downlight, 10 W, 1096 lm, 119 lm/W, with a medium 30 degree optic. Aluminium...

Mounting type: Recessed in ceiling

Material: Aluminium

Available colours: White RAL9010, black

Power: 10 W

Luminous flux: 1096 lm



ECO-LED-57150

Flexiray I Adjustable Recessed LED Spotlight 45W

Adjustable recessed LED spotlight, 45 W, with a black aluminium housing. Flux 4831-5706 lm depending on the...

Mounting type: Recessed in ceiling

Material: Aluminium

Colour: Black

Power: 45 W

Luminous flux: 4831 - 5706 lm

Interior Architectural Lighting



ECO-LED-57306

Laluna Magnetic Track Decorative LED Luminaire 5W

Decorative 5 W LED luminaire for a 48 V DC low-voltage magnetic track, with omnidirectional emission of...

Mounting type: Magnetic, on 48 V DC track

Material: Anodised aluminium

Colour: Black

Power: 5 W

Luminous flux: 617 lm



ECO-LED-57033

Taskray Suspended Office LED Luminaire 25W 1200 mm

Suspended linear LED luminaire of 1200 mm and 25 W for workstations, with 2241 lm, efficacy of 89 lm/W and CRI...

Mounting type: Suspended

Material: Aluminium

Colour: Black

Power: 25 W

Luminous flux: 2241 lm



ECO-LED-57610

Astraline G25 Slim Magnetic Track LED Luminaire 25W

Linear LED luminaire of 25 W with 25 LEDs, for a 48 V DC slim magnetic track. Flux 1699 lm, efficacy 68 lm/W, CRI 90,...

Mounting type: Magnetic, on 48 V DC slim track

Material: Aluminium

Colour: Black

Power: 25 W

Number of LEDs: 25



ECO-LED-57564

Astraline G15 Slim Magnetic Track LED Luminaire 15W

Linear LED luminaire of 15 W for a 48 V DC slim magnetic track, with 1049 lm, efficacy of 70 lm/W, CRI 90 and a 30...

Mounting type: Magnetic, on 48 V DC slim track

Material: Aluminium

Standard colour: Black

Power: 15 W

Luminous flux: 1049 lm

Interior Architectural Lighting



ECO-LED-57541

Astraline G10 Slim Magnetic Track LED Luminaire 10W

Linear LED luminaire of 10 W for a 48 V DC slim magnetic track, with a flux of 790 lm, efficacy of 72 lm/W, CRI 90 a...

Mounting type: Magnetic, on 48 V DC slim track

Material: Aluminium

Colour: Black

Power: 10 W

Luminous flux: 790 lm



ECO-LED-57287

Coobix 4 Surface-Mounted Ceiling LED Spotlight 10W White

Surface-mounted ceiling LED spotlight of 10 W, with a white aluminium cubic body of 62 x 62 x 70 mm. Flux 540-680 lm...

Mounting type: Surface mounted on ceiling

Material: Aluminium

Colour: RAL9010 white

Power: 10 W

Luminous flux: 540-680 lm



ECO-LED-57268

Coobix 3 Surface-Mounted Ceiling LED Spotlight 8W White

Surface-mounted ceiling LED spotlight, 8 W, in a white aluminium body of 86 x 35 x 70 mm. Flux 390-480 lm...

Mounting type: Surface-mounted on ceiling

Material: Aluminium

Colour: RAL9010 white

Power: 8 W

Luminous flux: 390-480 lm



ECO-LED-57211

Arcadia T Surface-Mounted LED Wall Washer 10W

Surface-mounted ceiling LED luminaire, 10 W, with a wall washer optic for even vertical illumination. Flux 944 lm,...

Mounting type: Surface-mounted on ceiling

Material: Aluminium

Colour: Black

Power: 10 W

Luminous flux: 944 lm

Interior Architectural Lighting



ECO-LED-57226

Arcadia A Adjustable Surface-Mounted LED Spotlight 16W

Adjustable surface-mounted ceiling LED spotlight, 16 W, with 1471-1712 lm and CRI 90. Narrow, medium or wide opti...

Mounting type: Surface-mounted on ceiling, adjustable
Material: Aluminium
Colour: Black
Power: 16 W
Luminous flux: 1471-1712 lm




ECO-LED-57652

Astraline T Adjustable Linear LED Luminaire 10W Magnetic Track

Adjustable linear luminaire of 235 mm for slim 48 V DC magnetic track, with a 30 degree medium optic for...

Type: Adjustable linear LED luminaire for slim magnetic track
Mounting: On slim magnetic track, indoor
Material: Aluminium
Colour: Black
Power: 10 W



ECO-LED-57633

Astraline M Linear LED Luminaire 20W for Slim Magnetic Track

Diffuse linear luminaire of 615 mm for slim 48 V DC magnetic track, with omnidirectional 100 degree emission for ambient...

Type: Linear LED luminaire for slim magnetic track
Mounting: On slim magnetic track, indoor
Material: Aluminium
Colour: Black
Power: 20 W



ECO-LED-62806

Arvio 5 Multi-Prismatic Linear LED Luminaire 55W

Linear luminaire of 1496 mm in extruded aluminium with an anti-glare multi-prismatic diffuser, for offices, institutio...

Type: Linear LED luminaire, multi-prismatic diffuser
Mounting: Surface / suspended
Material: Extruded aluminium
Colours: White RAL 9010 / Black
Power: 55 W

Interior Architectural Lighting



ECO-LED-62787

Arvio 4 Multi-Prismatic Linear LED Luminaire 44W

Linear luminaire of 1198 mm in extruded aluminium, with an anti-glare multi-prismatic diffuser for offices and retail....

Type: Linear LED luminaire, multi-prismatic diffuser

Mounting: Surface / suspended

Material: Extruded aluminium

Colours: White RAL 9010 / Black

Power: 44 W



ECO-LED-64315

Arcadia R Adjustable Surface-Mounted LED Spotlight 15W

Surface-mounted ceiling spotlight with an adjustable head, 15 W, medium 36 degree optic, for accent lighting in...

Type: Surface-mounted LED spotlight, adjustable

Mounting: Surface-mounted on ceiling, indoor

Housing material: Aluminium

Colours: White RAL 9010 / Black
Power: 15 W



ECO-LED-64338

Arcadia L Surface-Mounted LED Spotlight 10W Interchangeable Optics

Cylindrical surface-mounted ceiling spotlight, 100 x 70 mm, 10 W, with interchangeable optics: medium, wide, extra...

Type: Surface-mounted cylindrical LED spotlight

Mounting: Surface-mounted on ceiling, indoor

Housing material: Aluminium

Colour: White RAL 9010

Power: 10 W



ECO-LED-455

Titan 48 Industrial LED Floodlight 240W, Adjustable

Configurable industrial floodlight with 12, 24, 36 or 48 high-power OSRAM LEDs, in 30-50W, 60-100W, 100-150W an...

Body material: Electrostatically painted aluminium

Body colour: Standard grey

Light source: High-power OSRAM LEDs

Number of LEDs: 12 | 24 | 36 | 48

Interior Architectural Lighting



ECO-LED-393

Display Line III LED Luminaire 1 Module 13W, Surface-Mounted

Modular linear luminaire with Samsung SMD LEDs grouped in modules of 20 LEDs and 12.5W, from 1 to 5 modules (300-15...

Body material: Anodised aluminium

Diffuser: Multi-prismatic or 3 mm clear polycarbonate

Body colour: Other colours available on request

Light source: Samsung SMD

08

Exterior Architectural Lighting

Exterior architectural families for facades, colonnades, landscapes and urban spaces: linear wall washers, projectors, in-ground and step luminaires engineered for heat, dust and coastal exposure. Marine-grade finishes, IP67 and IP68 sealing and stainless fixings keep performance stable in Gulf conditions.

32 products in this family. Individual datasheets available on www.ecosolaris.ae.

Exterior Architectural Lighting



ECO-LED-56904

Topaz 24 Street LED Luminaire 120W

120 W pole-mounted street luminaire with an extruded aluminium housing of 586 x 248 x 63 mm and an adjusta...

Mounting type: Pole mounted, adjustable

Material: Extruded aluminium

Finish: Grey RAL7040, electrostatic powder coated

Power: 120 W

Luminous flux: 14673-15487 lm



ECO-LED-56943

Linea N Flexible LED Neon 7.2W Outdoor IP67

Flexible neon cast in silicone, 15 x 15 mm, supplied in 5000 mm lengths, with 168 LEDs per metre and omnidirectional...

Mounting type: In a 1 m aluminium profile (accessory) or directly on the substrate

Material: Cast silicone

Finish: Grey RAL7040

Power: 7.2 W

Luminous flux: 440 lm



ECO-LED-57789

Helios Window LED Floodlight 5-7.6W Outdoor

Compact polycarbonate facade floodlight, 130 x 90 x 55 mm, with an elliptical optic for outlining windows and niches...

Mounting type: Surface mounted, fixed

Material: Polycarbonate

Finish: Black

Power: 5 W / 7.5 W / 7.6 W

Luminous flux: 481-893 lm



ECO-LED-55904

Galaxy 2 Adjustable Linear LED Luminaire 3.2-5.6W Outdoor

Compact outdoor linear projector, 3.2 W or 5.6 W, with an extruded aluminium housing of 83 x 58 x 101 mm and...

Mounting type: Surface mounted on ceiling, floor or wall, adjustable

Material: Extruded aluminium; metal end caps (BK) or plastic (standard)

Available Finish: RAL 7040

Exterior Architectural Lighting



ECO-LED-56616

Andromeda 6 Adjustable LED Floodlight 8-14W Outdoor

Compact adjustable LED floodlight for outdoor accents. 8 to 14.3 W, 864 to 1823 lm, 108 to 127 lm/W. Extruded...

Mounting type: Adjustable floodlight, surface or pole mounted

Housing material: Extruded aluminium

Colour: Black (RAL9010)

Power range: 8 W - 14.3 W



ECO-LED-56721

Andromeda 36 Adjustable LED Floodlight 44-86W Outdoor

Adjustable outdoor floodlight for facades and large surfaces. 44.1 to 86.4 W, 5016 to 10473 lm, 106 to 129 lm/W. Extrude...

Mounting type: Adjustable outdoor floodlight

Housing material: Extruded aluminium

Colour: Black (RAL9010)

Power range: 44.1 W - 86.4 W

Luminous flux: 5016 - 10473 lm



ECO-LED-56686

Andromeda 24 Adjustable LED Floodlight 29.4-57.6W Outdoor

Adjustable outdoor floodlight of 437x135x170 mm in black extruded aluminium, with integral power supply and pol...

Mounting type: Adjustable, pole mounted

Material: Extruded aluminium

Colour: RAL9010 black

Power: 29.4 W / 57.6 W

Luminous flux: 3345-3808 lm

(33.4 W) 3345 3808 lm (57.6 W)



ECO-LED-56651

Andromeda 12 Adjustable LED Floodlight 14.7-28.8W Outdoor

Adjustable outdoor floodlight of 250x135x170 mm in black extruded aluminium, with integral power supply and pol...

Mounting type: Adjustable, pole mounted

Material: Extruded aluminium

Colour: RAL9010 black

Power: 14.7 W / 28.8 W

Luminous flux: 1672-1904 lm

(14.7 W) 1672 1904 lm (28.8 W)

Exterior Architectural Lighting



ECO-LED-56409

Galaxy 10 Adjustable Linear LED Luminaire 15-26W Outdoor

Outdoor linear luminaire in extruded aluminium, 83x58x377 mm, with integral driver and 220-240 V AC...

Mounting type: Surface mounted, adjustable (ceiling, floor, wall)

Material: Extruded aluminium
Colours: RAL7040 anodised silver, RAL7040 powder-coated grey, RAL9001 anodised black



ECO-LED-56460

Galaxy 10 1m Adjustable Linear LED Luminaire 15-26W Outdoor

Outdoor linear LED luminaire, 1000 x 83 x 58 mm, adjustable in the horizontal plane, 15 or 26 W, 1660 to 3768 lm, 108 t...

Mounting type: Ceiling, floor or wall, adjustable

Mounting bracket: BK (-50 degrees / +90 degrees, metal end caps) or standard (-90 degrees / +90 degrees, plastic end caps)



ECO-LED-57253

Arcadia D Surface-Mounted LED Spotlight 15W IP54 Outdoor

Surface-mounted ceiling LED spotlight, 15 W, rated IP54 for covered damp areas. Flux 1418-1502 lm, efficacy 108-...

Mounting type: Surface-mounted on ceiling

Material: Aluminium

Colour: Black

Power: 15 W

Luminous flux: 1418-1502 lm



ECO-LED-56284

Proton STII 108 Adjustable LED Floodlight 180W Outdoor

Outdoor LED floodlight of 180 W, with 23269-25272 lm and 129-140 lm/W depending on the optic. Extruded aluminium...

Mounting type: Pole, bracket or flat surface

Material: Extruded aluminium

Colour: RAL7040 grey, electrostatic powder coated

Power: 180 W

Luminous flux: 23269-25272 lm

Exterior Architectural Lighting



ECO-LED-62201

Astro II Mono Petrol Station LED Floodlight 50W

LED floodlight of 50 W for recessed mounting in fuel station canopies. It delivers 7056 lm at 141 lm/W, with a...

Mounting type: Recessed in canopy

Material: Extruded aluminium, UV-protected diffuser

Colour: RAL7040 grey

Power: 50 W

Luminaire flux: 7056 lm



ECO-LED-61913

Astro II Duo Recessed LED Canopy Luminaire 100W for Petrol Stations

Large-format recessed luminaire (520 x 355 mm) for fuel station canopies: 100 W, 14112 lm, 141 lm/W, wide 90...

Type: Recessed LED luminaire for canopies

Mounting: Recessed in canopy, outdoor

Housing material: Extruded aluminium

Diffuser: UV-protected



ECO-LED-56965

Up&Down Bidirectional LED Wall Light 2x7.5W Outdoor

Wall luminaire with up and down emission, 2x7.5 W and a wide optic, for functional lighting of facades and acces...

Type: Bidirectional LED wall light

Mounting: Surface-mounted on wall, outdoor

Housing material: Die-cast aluminium

Colour: Black

Power: 2x7.5 W



ECO-LED-56980

FlexiBeam Bidirectional LED Wall Light 2x5W Adjustable Beam Angle

Wall luminaire with two 5 W LED modules and a beam angle adjustable between 15 and 120 degrees, for residential and...

Type: Bidirectional LED wall light, adjustable angle

Mounting: Surface-mounted on wall, outdoor

Housing material: Aluminium

Colour: Black

Power: 2x5 W

Exterior Architectural Lighting



ECO-LED-56950

Celestial Bidirectional LED Wall Light 2x3W Outdoor

Wall luminaire with bidirectional up and down emission and an elliptical optic, for accent lighting of facades....

Type: Bidirectional LED wall light

Mounting: Surface-mounted on wall, outdoor

Housing material: Die-cast aluminium

Colour: Black

Power: 2x3 W



ECO-LED-241

Proton STII 54 Street LED Floodlight 90W

High output street floodlight with 54 OSRAM LEDs, 135 W and a luminous flux of 16,500 lm, designed for ME4 class...

Housing material: Extruded aluminium, electrostatically powder coated

Diffuser: 3 mm clear polycarbonate, UV protected

Housing colour: Grey (standard)



ECO-LED-292

Astro 54 Recessed LED Luminaire 90W for Petrol Stations

Floodlight with 54 high-power OSRAM LEDs, 135W, for recessed mounting in the canopy of petrol stations, ove...

Body material: Electrostatically painted aluminium

Diffuser: Clear polycarbonate, UV protected

Body colour: Other colours available on request

Light source: 54 high power



ECO-LED-290

Astro 36 Recessed LED Luminaire 60W for Fuel Stations

Floodlight for fuel station canopies with 36 high-power OSRAM LEDs (100 W), wide distribution and dedicated...

Housing material: Powder-coated aluminium

Housing colour: Other colours on customer request

Diffuser: Clear polycarbonate, UV protected

Light source: High power

Exterior Architectural Lighting



ECO-LED-249

Astro 45 Recessed LED Luminaire 75W for Fuel Stations

Floodlight for fuel station canopies with 45 high-power OSRAM LEDs (120 W), wide distribution and dedicated...

Housing material: Powder-coated aluminium

Housing colour: Other colours on request

Diffuser: Clear polycarbonate, UV protected

Light source: High power



ECO-LED-40

Astro 24 Recessed LED Luminaire 40W for Fuel Stations

Floodlight for fuel station canopies with 24 high-power OSRAM LEDs (80 W), wide distribution and dedicated...

Housing material: Powder-coated aluminium

Housing colour: Other colours on customer request

Diffuser: Clear polycarbonate, UV protected

Light source: High power



ECO-LED-11

Atlas 6 Recessed In-Ground LED Luminaire 8-14W

Flat recessed floodlight of 130 x 60 mm with 6 OSRAM LEDs, at 6W (1W LEDs) or 15W (2.5W LEDs), black housing, for...

Housing material: Powder-coated aluminium

Housing colour: Black, standard

Flanges: Stainless steel

Diffuser: 8 mm toughened glass

Number of LEDs: 6 (OSRAM)



ECO-LED-10

Atlas 5 Linear Recessed In-Ground LED Luminaire 7-12W

Flat recessed floodlight of 130 x 60 mm with 5 OSRAM LEDs of 1W or 2.5W, black aluminium housing, for in-ground lightin...

Housing material: Powder-coated aluminium

Housing colour: Black, standard

Flanges: Stainless steel

Diffuser: 8 mm toughened glass

Number of LEDs: 5 (OSRAM)

Exterior Architectural Lighting



ECO-LED-9

Atlas 3 Recessed In-Ground LED Luminaire 5-7.6W

Outdoor recessed floodlight of 90 x 92.5 mm with 3 OSRAM LEDs, at 3W (1W LEDs) or 7.5W (2.5W LEDs), for recessed...

Housing material: Powder-coated aluminium

Housing colour: Other colours available on customer request

Flanges: Stainless steel

Diffuser: 8 mm toughened glass
Number of LEDs: 3 (OSRAM)



ECO-LED-7

Saturn 6 Adjustable LED Floodlight 8-14.2W Outdoor

Adjustable decorative floodlight of 100 x 130 mm with 6 OSRAM LEDs, at 6W (1W LEDs) or 15W (2.5W LEDs), black aluminium...

Housing material: Powder-coated aluminium

Housing colour: Black, standard

Flanges: Stainless steel

Diffuser: 8 mm toughened glass
Number of LEDs: 6 (OSRAM)



ECO-LED-6

Saturn 5 Adjustable LED Floodlight 7-12W Outdoor

Adjustable decorative floodlight of 130 x 114 mm with 5 OSRAM LEDs, at 5W (1W LEDs) or 12.5W (2.5W LEDs), black...

Housing material: Powder-coated aluminium

Housing colour: Black, standard

Flanges: Stainless steel

Diffuser: 8 mm toughened glass
Number of LEDs: 5 (OSRAM)



ECO-LED-5

Saturn 3 Adjustable LED Floodlight 5-7.6W Outdoor

Adjustable decorative floodlight of 100 x 90 mm with 3 OSRAM LEDs, at 3W (1W LEDs) or 7.5W (2.5W LEDs), for architectural...

Housing material: Powder-coated aluminium

Flanges: Stainless steel

Diffuser: 8 mm toughened glass

Housing colour: Other colours available on customer request
Number of LEDs: 3 (OSRAM)

Exterior Architectural Lighting



ECO-LED-4

Galaxy 24 Adjustable Linear LED Luminaire 32-61W Outdoor

Linear floodlight of 920 mm with 24 OSRAM LEDs, at 24W (1W LEDs) or 60W (2.5W LEDs), for architectural lighting of...

Housing material: Powder-coated aluminium

Housing colour: Grey, standard; other colours on customer request

Fixing system: Powder-coated aluminium, adjustable by rotation



ECO-LED-3

Galaxy 16 Adjustable Linear LED Luminaire 21-40W Outdoor

Outdoor linear floodlight of 620 mm with 16 OSRAM LEDs, at 16W (1W LEDs) or 40W (2.5W LEDs), for architectural, gene...

Housing material: Powder-coated aluminium

Housing colour: Grey, standard; other colours on customer request

Fixing system: Powder-coated aluminium, adjustable by rotation



ECO-LED-2

Galaxy 8 Adjustable Linear LED Luminaire 10.8-20W Outdoor

Outdoor linear floodlight with 8 OSRAM LEDs, available at 8W (1W LEDs) or 20W (2.5W LEDs), for architectural lighting of...

Housing material: Powder-coated aluminium

Housing colour: Grey, standard; other colours on customer request

Fixing system: Powder-coated aluminium, adjustable by rotation



ECO-LED-1

Galaxy 4 Adjustable Linear LED Luminaire 6.7-12W Outdoor

Linear floodlight with 4 LEDs for architectural lighting, the most compact model in the Galaxy series. It mounts on...

Luminaire type: Outdoor linear floodlight

Series: Galaxy

Number of LEDs: 4

Lighting type: Architectural

Mounting: On facades



Let us light your project

Lighting design, photometric studies, supply and installation across the UAE.

Contact us for a project quotation and current lead times.

PHOTOVOLTAIC ENERGY L.L.C.

Canal Highs 4001, P.O. Box 25314, Dubai, UAE

www.ecosolaris.ae · contact@ecosolaris.ae · Tel / WhatsApp: +971 58 511 8662

Informative document. Specifications may be updated without prior notice. Images are illustrative.